

Dam: Bursa Uludag

Country Turkey

River Kirkpinarlar

40°6'26.72"N 29°9'3.36"E

40.107422 29.150934

Owner/Client DSI - State Hydraulic Works

Designer/Engineer Unknown

Contractor Unknown

Purpose (code) F W

Site start 07.10.2021

RCC start 01.01.2022

RCC completion 31.08.2023

Site completion 25.10.2023

Height (m) 28

Length (m) 168

Volume of RCC ($\text{m}^3 \times 10^3$) Unknown

Total volume ($\text{m}^3 \times 10^3$) 60

Reservoir capacity ($\text{m}^3 \times 10^6$) 1

Upstream slope Unknown

Forming of upstream face (code) Unknown

Downstream slope Unknown

Forming of downstream face (code) Unknown

Spillway slope Unknown

Forming of spillway face (code) Unknown

Depth of layers (mm) Unknown

Depth of lifts (mm) Unknown

Cement content (kg/m^3) Unknown

Pozzolan content (kg/m^3) Unknown

Code for pozzolan Unknown

RCCDAM Unique Serial No. RCCDAM1225

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines