Dam:	Bouzina	Country	Algeria
River	*Unknown*	35°12'26.2"N 6°0'58.5"E	35.207279 6.01625
Owner/Client	ANBT (Agence Nationale des Barrages et Transferts)		
Designer/Engineer	ISL		
Contractor	Ilci, Gunsail Insaat, ETRHB Hadad J.V.		

Purpose (code)	I W
Site start	01.01.2014
RCC start	01.02.2018
RCC completion	31.07.2019
Site completion	01.01.2023
Height (m)	77
Length (m)	177
Volume of RCC (m^3x10^3)	250
Total volume (m^3x10^3)	330
Reservoir capacity (m^3x10^6)	18
Upstream slope	V
Forming of upstream face (code)	(1)
Downstream slope	0.89
Forming of downstream face (code)	(1) *
Spillway slope	0.89
Forming of spillway face (code)	(12)
Depth of layers (mm)	300
Depth of lifts (mm)	300
Cement content (kg/m^3)	110 77
Pozzolan content (kg/m^3)	0 33
Code for pozzolan	(F)
RCCDAM Unique Serial No.	RCCDAM1256

Guide to Abbreviations

Purpose

E	Environmental
F	Flood control
G	Groundwater recharge
H	Flood control
I	Irrigation
N	Navigation
P	Pollution control
R	Recreation
W	Water supply

Facing method

(1)	Traditional concrete against formwork
(2)	Traditional concrete against formwork with external geomembrane
(3)	RCC against formwork
(4)	RCC against formwork with external geomembrane
(5)	Traditional concrete against precast concrete panels
(6)	Traditional concrete against precast concrete panels with geomembrane
(7)	RCC against precast concrete panels
(8)	RCC against precast concrete panels with geomembrane
(9)	RCC against precast concrete panels with hot poured membrane
(10)	RCC against precast concrete blocks
(11)	Reinforced conventional concrete cast before RCC placement
(12)	Reinforced conventional concrete cast after RCC placement
(13)	Reinforced concrete cast against precast units or slip-formed facing elements
(14)	Slip-formed/extruded facing elements
(15)	RCC supported by fill shoulders
(16)	Mechanically compacted unformed face of RCC
(17)	Unformed face of RCC
'	GEVR/GE-RCC
*	Stepped face

Pozzolans

(-)	No Pozzolan Used
(C)	High-lime flyash (ASTM Class C)
(F)	Low-lime flyash (ASTM Class F)
(M)	Milled sand
(N)	Natural pozzolan (ASTM Class N)
(R)	ROLAC (mixture of flyash and slag with or without limestone fines)
(S)	Ground-granulated blast-furnace slag
(L)	Mixture of GGBFS and limestone fines