

Dam: Clifford D. Craig (formerly Spring Hollow)

Country USA

River off-stream

37°13'52.01"N 80°10'33.98"W

37.231113 -80.176109

Owner/Client Western Virginia Water Authority

Designer/Engineer Hayes, Seay, Mattern, Mattern

Contractor Unknown

Purpose (code) W

Site start 01.10.1992

RCC start 01.03.1993

RCC completion 30.08.1993

Site completion 31.12.1994

Height (m) 74

Length (m) 302

Volume of RCC (m³x10³) 222

Total volume (m³x10³) 223

Reservoir capacity (m³x10⁶) 12

Upstream slope V

Forming of upstream face (code) (6)

Downstream slope 0.80

Forming of downstream face (code) (17)

Spillway slope none

Forming of spillway face (code) Unknown

Depth of layers (mm) 300

Depth of lifts (mm) 300

Cement content (kg/m³) 53

Pozzolan content (kg/m³) 53

Code for pozzolan (F)

RCCDAM Unique Serial No. RCCDAM0122

Under Construction



RCCDAM0122UC

Completed Dam



RCCDAM0122CD

Google Earth



RCCDAM0122GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines