

Dam: Dong Nai 2

Country Vietnam

River Dong Nai

11°42'46.56"N 108°03'27.34"E

11.713083 108.057884

Owner/Client Trung Nam Power Jointstock Company

Designer/Engineer PECC1 (Power Engineering Consulting Company N°1)

Contractor Trung Nam Engineering and Construction Jointstock Company

Purpose (code) H

Site start 01.04.2009

RCC start 01.12.2010

RCC completion 01.05.2012

Site completion 01.03.2013

Height (m) 80

Length (m) 429

Volume of RCC (m³x10³) 786

Total volume (m³x10³) 1025

Reservoir capacity (m³x10⁶) 281

Upstream slope Unknown

Forming of upstream face (code) Unknown

Downstream slope Unknown

Forming of downstream face (code) (3') *

Spillway slope Unknown

Forming of spillway face (code) Unknown

Depth of layers (mm) 300

Depth of lifts (mm) 300

Cement content (kg/m³) 80
90

Pozzolan content (kg/m³) 120
110

Code for pozzolan (N)

RCCDAM Unique Serial No. RCCDAM0540

Google Earth



RCCDAM0540GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines