

Dam: Duas Serras

Country: Brazil

River: Duas Serras

8°13'48.23"S 36°43'10.20"W

-8.230064 -36.719501

Owner/Client: *Unknown*

Designer/Engineer: *Unknown*

Contractor: *Unknown*

Purpose (code): F

Site start: 01.01.2005

RCC start: 01.01.2006

RCC completion: 31.12.2007

Site completion: 31.12.2008

Height (m): 19

Length (m): 113

Volume of RCC (m³x10³): 6

Total volume (m³x10³): *Unknown*

Reservoir capacity (m³x10⁶): 2

Upstream slope:

Forming of upstream face (code):

Downstream slope:

Forming of downstream face (code):

Spillway slope:

Forming of spillway face (code):

Depth of layers (mm): 300

Depth of lifts (mm): 300

Cement content (kg/m³):

Pozzolan content (kg/m³):

Code for pozzolan:

RCCDAM Unique Serial No.: RCCDAM0398

Google Earth



RCCDAM0398GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines