

Dam: El Maleh Amont

Country Morocco

River Maleh

33°30'19.34"N 7°20'33.31"W

33.505371 -7.342586

Owner/Client Direction des Aménagements Hydrauliques

Designer/Engineer Ingema

Contractor Direction des Aménagements Hydrauliques

Purpose (code) F

Site start 01.01.2007

RCC start 29.09.2007

RCC completion 30.06.2011

Site completion 30.10.2012

Height (m) 49

Length (m) 174

Volume of RCC ($m^3 \times 10^3$) 100

Total volume ($m^3 \times 10^3$) 140

Reservoir capacity ($m^3 \times 10^6$) 35

Upstream slope 0.20

Forming of upstream face (code) (5)

Downstream slope 0.60

Forming of downstream face (code) (5)

Spillway slope 0.60

Forming of spillway face (code) (5)

Depth of layers (mm) 300

Depth of lifts (mm) 300

Cement content (kg/m^3) 120

Pozzolan content (kg/m^3) 0

Code for pozzolan (-)

RCCDAM Unique Serial No. RCCDAM0443

Completed Dam



RCCDAM0443CD

Google Earth



RCCDAM0443GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines