

Dam: El Realito

Country Mexico

River Santa Maria

21°36'25.96"N 100°14'9.57"W

21.60721 -100.235992

Owner/Client CNA (Comisión Nacional del Agua)

Designer/Engineer Technoproject

Contractor Grupo Carso/Carlo (La Constructora de Infraestructuras Latino Americana)

Purpose (code)

Site start 01.01.2008

RCC start 01.07.2009

RCC completion 30.06.2011

Site completion 31.12.2011

Height (m) 85

Length (m) 270

Volume of RCC ($m^3 \times 10^3$) 420

Total volume ($m^3 \times 10^3$) *Unknown*

Reservoir capacity ($m^3 \times 10^6$) 57

Upstream slope V

Forming of upstream face (code) (1)

Downstream slope 0.85

Forming of downstream face (code) *Unknown*

Spillway slope 0.85

Forming of spillway face (code) *Unknown*

Depth of layers (mm) 300

Depth of lifts (mm) 300


Cement content (kg/m^3) 33 to 66

Pozzolan content (kg/m^3) 27 to 54

Code for pozzolan (S)

RCCDAM Unique Serial No. RCCDAM0501

Under Construction



RCCDAM0501UC

Completed Dam



RCCDAM0501CD

Google Earth



RCCDAM0501GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines