

Dam: Juba I

Country Brazil

River Juba

14°44'24.85"S 58°6'11.6"W

-14.740236 -58.103222

Owner/Client Itamarati Norte S.A. (part of Brennand Energia)

Designer/Engineer Unknown

Contractor Constran International

Purpose (code) H

Site start 01.01.1993

RCC start 01.01.1994

RCC completion 31.12.1995

Site completion 31.12.1995

Height (m) 21

Length (m) 238

Volume of RCC (m<sup>3</sup>x10<sup>3</sup>) 96

Total volume (m<sup>3</sup>x10<sup>3</sup>) 113

Reservoir capacity (m<sup>3</sup>x10<sup>6</sup>) Unknown

Upstream slope Unknown

Forming of upstream face (code) Unknown

Downstream slope Unknown

Forming of downstream face (code) Unknown

Spillway slope Unknown

Forming of spillway face (code) Unknown

Depth of layers (mm) Unknown

Depth of lifts (mm) Unknown

Cement content (kg/m<sup>3</sup>) 60

Pozzolan content (kg/m<sup>3</sup>) 15

Code for pozzolan (N)

RCCDAM Unique Serial No. RCCDAM0815

# Guide to Abbreviations

## Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

## Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
  - ' GEVR/GE-RCC
  - \* Stepped face

## Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines