Dam:	Karkheh (Pie Pol)	Country	Iran
River	Karkeh	32°29'21.86"N 48°07'8.81"E	32.489407 48.119114
Owner/Client	Khuzestan Water & Energy Authority		
Designer/Engineer	Mahab Ghodss		
Contractor	Jahan Kowsar Co		

Purpose (code)	F H
Site start	08.02.1998
RCC start	01.07.1999
RCC completion	31.07.2000
Site completion	31.12.2001
Height (m)	34
Length (m)	350
Volume of RCC (m^3x10^3)	130
Total volume (m^3x10^3)	270
Reservoir capacity (m^3x10^6)	40
Upstream slope	*Unknown*
Forming of upstream face (code)	(12)
Downstream slope	*Unknown*
Forming of downstream face (code)	(12)
Spillway slope	ogee
Forming of spillway face (code)	(12)
Depth of layers (mm)	300
Depth of lifts (mm)	300
Cement content (kg/m^3)	97
Pozzolan content (kg/m^3)	33
Code for pozzolan	(-)
RCCDAM Unique Serial No.	RCCDAM0236

Completed Dam



RCCDAM0236CD

Google Earth



RCCDAM0236GE

Guide to Abbreviations

Purpose

E	Environmental
F	Flood control
G	Groundwater recharge
H	Flood control
I	Irrigation
N	Navigation
P	Pollution control
R	Recreation
W	Water supply

Facing method

(1)	Traditional concrete against formwork
(2)	Traditional concrete against formwork with external geomembrane
(3)	RCC against formwork
(4)	RCC against formwork with external geomembrane
(5)	Traditional concrete against precast concrete panels
(6)	Traditional concrete against precast concrete panels with geomembrane
(7)	RCC against precast concrete panels
(8)	RCC against precast concrete panels with geomembrane
(9)	RCC against precast concrete panels with hot poured membrane
(10)	RCC against precast concrete blocks
(11)	Reinforced conventional concrete cast before RCC placement
(12)	Reinforced conventional concrete cast after RCC placement
(13)	Reinforced concrete cast against precast units or slip-formed facing elements
(14)	Slip-formed/extruded facing elements
(15)	RCC supported by fill shoulders
(16)	Mechanically compacted unformed face of RCC
(17)	Unformed face of RCC
'	GEVR/GE-RCC
*	Stepped face

Pozzolans

(-)	No Pozzolan Used
(C)	High-lime flyash (ASTM Class C)
(F)	Low-lime flyash (ASTM Class F)
(M)	Milled sand
(N)	Natural pozzolan (ASTM Class N)
(R)	ROLAC (mixture of flyash and slag with or without limestone fines)
(S)	Ground-granulated blast-furnace slag
(L)	Mixture of GGBFS and limestone fines