Dam:	Kasegawa auxiliary dam	Country	Japan
River	Kase	33°24'57.06"N 130°12'10.68"E	33.415852 130.202972
Owner/Client	Ministry of Land, Infrastructure, Transport and Tourism		
Designer/Engineer	Yachiyo Engineering		
Contractor	Nishimatsu Construction Co.		

Purpose (code)	F H I W
Site start	04.03.2008
RCC start	01.10.2009
RCC completion	02.06.2010
Site completion	30.09.2010
Height (m)	29
Length (m)	116
Volume of RCC (m^3x10^3)	52
Total volume (m^3x10^3)	68
Reservoir capacity (m^3x10^6)	1
Upstream slope	0.80
Forming of upstream face (code)	(12)
Downstream slope	0.80
Forming of downstream face (code)	(12)
Spillway slope	0.80
Forming of spillway face (code)	(12)
Depth of layers (mm)	250
Depth of lifts (mm)	750
Cement content (kg/m^3)	80
Pozzolan content (kg/m^3)	0
Code for pozzolan	(-)
RCCDAM Unique Serial No.	RCCDAM0464

Google Earth



RCCDAM0464GE

Guide to Abbreviations

Purpose

E	Environmental
F	Flood control
G	Groundwater recharge
H	Flood control
I	Irrigation
N	Navigation
P	Pollution control
R	Recreation
W	Water supply

Facing method

(1)	Traditional concrete against formwork
(2)	Traditional concrete against formwork with external geomembrane
(3)	RCC against formwork
(4)	RCC against formwork with external geomembrane
(5)	Traditional concrete against precast concrete panels
(6)	Traditional concrete against precast concrete panels with geomembrane
(7)	RCC against precast concrete panels
(8)	RCC against precast concrete panels with geomembrane
(9)	RCC against precast concrete panels with hot poured membrane
(10)	RCC against precast concrete blocks
(11)	Reinforced conventional concrete cast before RCC placement
(12)	Reinforced conventional concrete cast after RCC placement
(13)	Reinforced concrete cast against precast units or slip-formed facing elements
(14)	Slip-formed/extruded facing elements
(15)	RCC supported by fill shoulders
(16)	Mechanically compacted unformed face of RCC
(17)	Unformed face of RCC
'	GEVR/GE-RCC
*	Stepped face

Pozzolans

(-)	No Pozzolan Used
(C)	High-lime flyash (ASTM Class C)
(F)	Low-lime flyash (ASTM Class F)
(M)	Milled sand
(N)	Natural pozzolan (ASTM Class N)
(R)	ROLAC (mixture of flyash and slag with or without limestone fines)
(S)	Ground-granulated blast-furnace slag
(L)	Mixture of GGBFS and limestone fines