

Dam: Longmentan N^o1

Country China

River Chanxi

25°29'32.65"N 118°21'17.91"E

25.492403 118.354973

Owner/Client Dehua County, Fujian Province

Designer/Engineer Fujian Institute of Investigation and Design of Water Conservancy and Hydropower

Contractor Fujian (Minjiang) Construction Bureau

Purpose (code) H I W

Site start 01.12.1985

RCC start 01.12.1987

RCC completion 31.08.1989

Site completion 30.09.1989

Height (m) 58

Length (m) 150

Volume of RCC (m³x10³) 71

Total volume (m³x10³) 93

Reservoir capacity (m³x10⁶) 53

Upstream slope V
0.30

Forming of upstream face (code) (12)
(12)

Downstream slope 0.75

Forming of downstream face (code) (10)

Spillway slope 0.75

Forming of spillway face (code) (13)

Depth of layers (mm) 300

Depth of lifts (mm) 300

Cement content (kg/m³) 72
54

Pozzolan content (kg/m³) 82
86

Code for pozzolan (F)

RCCDAM Unique Serial No. RCCDAM0056

Completed Dam



RCCDAM0056CD

Google Earth



RCCDAM0056GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines