

Dam: Manduriacu

Country Ecuador

River Mauduriacu

0°12'50.61"N 78°54'44.97"W

0.214058 -78.912491

Owner/Client *Unknown*

Designer/Engineer Typsa, Spain

Contractor Odebrecht

Purpose (code) H

Site start 01.12.2011

RCC start 01.01.2013

RCC completion 31.12.2014

Site completion 19.03.2015

Height (m) 61

Length (m) 245

Volume of RCC (m<sup>3</sup>x10<sup>3</sup>) 114

Total volume (m<sup>3</sup>x10<sup>3</sup>) *Unknown*

Reservoir capacity (m<sup>3</sup>x10<sup>6</sup>) 10

Upstream slope 0.25

Forming of upstream face (code)

Downstream slope 0.75

Forming of downstream face (code)

Spillway slope 0.75

Forming of spillway face (code)

Depth of layers (mm)

Depth of lifts (mm)

Cement content (kg/m<sup>3</sup>)

Pozzolan content (kg/m<sup>3</sup>)

Code for pozzolan (N)

RCCDAM Unique Serial No. RCCDAM0627

### Under Construction



RCCDAM0627UC

### Completed Dam



RCCDAM0627CD

### Google Earth



RCCDAM0627GE

# Guide to Abbreviations

## Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

## Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
  - ' GEVR/GE-RCC
  - \* Stepped face

## Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines