

Dam: Olivenhain Country USA

River Escondido Creek 33°04'13.21"N 117°08'17.51"W 33.070335 -117.138199

Owner/Client San Diego County Water Authority

Designer/Engineer Parsons-Harza JV.

Contractor Kiewit Pacific Co. Ltd.

Purpose (code) W

Site start 13.06.2001

RCC start 04.02.2002

RCC completion 31.10.2002

Site completion 03.07.2003

Height (m) 97

Length (m) 788

Volume of RCC (m³x10³) 1070

Total volume (m³x10³) 1140

Reservoir capacity (m³x10⁶) 30

Upstream slope V

Forming of upstream face (code) (4')

Downstream slope 0.80

Forming of downstream face (code) (3) *

Spillway slope 0.80

Forming of spillway face (code) (1) *

Depth of layers (mm) 300

Depth of lifts (mm) 300

Cement content (kg/m³) 74

Pozzolan content (kg/m³) 121

Code for pozzolan (F)

RCCDAM Unique Serial No. RCCDAM0282

Under Construction



RCCDAM0282UC

Completed Dam



RCCDAM0282CD

Google Earth



RCCDAM0282GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines