Dam:	Picachos	Country	Mexico
River	Presidio	23°28'51.45"N 106°12'18.47"W	23.480959 -106.205132
Owner/Client	CNA (Comisión Nacional del Agua)		
Designer/Engineer	Intertechne		
Contractor	Andrade Gutierrez		

Purpose (code)	I W
Site start	01.02.2007
RCC start	01.09.2007
RCC completion	31.12.2008
Site completion	31.12.2009
Height (m)	85
Length (m)	256
Volume of RCC (m^3x10^3)	85
Total volume (m^3x10^3)	*Unknown*
Reservoir capacity (m^3x10^6)	322
Upstream slope	V 0.15
Forming of upstream face (code)	(12) (12)
Downstream slope	0.85
Forming of downstream face (code)	(12)
Spillway slope	0.85
Forming of spillway face (code)	(12)
Depth of layers (mm)	300
Depth of lifts (mm)	3000
Cement content (kg/m^3)	50
Pozzolan content (kg/m^3)	45
Code for pozzolan	(S)
RCCDAM Unique Serial No.	RCCDAM0435

Under Construction



RCCDAM0435UC

Completed Dam



RCCDAM0435CD

Google Earth



RCCDAM0435GE

Guide to Abbreviations

Purpose

E	Environmental
F	Flood control
G	Groundwater recharge
H	Flood control
I	Irrigation
N	Navigation
P	Pollution control
R	Recreation
W	Water supply

Facing method

(1)	Traditional concrete against formwork
(2)	Traditional concrete against formwork with external geomembrane
(3)	RCC against formwork
(4)	RCC against formwork with external geomembrane
(5)	Traditional concrete against precast concrete panels
(6)	Traditional concrete against precast concrete panels with geomembrane
(7)	RCC against precast concrete panels
(8)	RCC against precast concrete panels with geomembrane
(9)	RCC against precast concrete panels with hot poured membrane
(10)	RCC against precast concrete blocks
(11)	Reinforced conventional concrete cast before RCC placement
(12)	Reinforced conventional concrete cast after RCC placement
(13)	Reinforced concrete cast against precast units or slip-formed facing elements
(14)	Slip-formed/extruded facing elements
(15)	RCC supported by fill shoulders
(16)	Mechanically compacted unformed face of RCC
(17)	Unformed face of RCC
'	GEVR/GE-RCC
*	Stepped face

Pozzolans

(-)	No Pozzolan Used
(C)	High-lime flyash (ASTM Class C)
(F)	Low-lime flyash (ASTM Class F)
(M)	Milled sand
(N)	Natural pozzolan (ASTM Class N)
(R)	ROLAC (mixture of flyash and slag with or without limestone fines)
(S)	Ground-granulated blast-furnace slag
(L)	Mixture of GGBFS and limestone fines