Dam:	Pine Brook	Country	USA
River	*Unknown*	40°02'57.63"N 105°18'44.63"W	40.049343 -105.312393
Owner/Client	Pine Brook Water District		
Designer/Engineer	TCB Inc		
Contractor	ASI Constructors Inc		

Purpose (code)	W
Site start	01.01.2005
RCC start	25.10.2005
RCC completion	15.04.2006
Site completion	31.12.2006
Height (m)	26
Length (m)	170
Volume of RCC (m^3x10^3)	27
Total volume (m^3x10^3)	30
Reservoir capacity (m^3x10^6)	1
Upstream slope	V
Forming of upstream face (code)	(7)
Downstream slope	*Unknown*
Forming of downstream face (code)	(17)
Spillway slope	separate
Forming of spillway face (code)	*Unknown*
Depth of layers (mm)	300
Depth of lifts (mm)	300
Cement content (kg/m^3)	95
Pozzolan content (kg/m^3)	59
Code for pozzolan	(F)
RCCDAM Unique Serial No.	RCCDAM0354

Under Construction



RCCDAM0354UC

Completed Dam



RCCDAM0354CD

Google Earth



RCCDAM0354GE

Guide to Abbreviations

Purpose

E	Environmental
F	Flood control
G	Groundwater recharge
H	Flood control
I	Irrigation
N	Navigation
P	Pollution control
R	Recreation
W	Water supply

Facing method

(1)	Traditional concrete against formwork
(2)	Traditional concrete against formwork with external geomembrane
(3)	RCC against formwork
(4)	RCC against formwork with external geomembrane
(5)	Traditional concrete against precast concrete panels
(6)	Traditional concrete against precast concrete panels with geomembrane
(7)	RCC against precast concrete panels
(8)	RCC against precast concrete panels with geomembrane
(9)	RCC against precast concrete panels with hot poured membrane
(10)	RCC against precast concrete blocks
(11)	Reinforced conventional concrete cast before RCC placement
(12)	Reinforced conventional concrete cast after RCC placement
(13)	Reinforced concrete cast against precast units or slip-formed facing elements
(14)	Slip-formed/extruded facing elements
(15)	RCC supported by fill shoulders
(16)	Mechanically compacted unformed face of RCC
(17)	Unformed face of RCC
'	GEVR/GE-RCC
*	Stepped face

Pozzolans

(-)	No Pozzolan Used
(C)	High-lime flyash (ASTM Class C)
(F)	Low-lime flyash (ASTM Class F)
(M)	Milled sand
(N)	Natural pozzolan (ASTM Class N)
(R)	ROLAC (mixture of flyash and slag with or without limestone fines)
(S)	Ground-granulated blast-furnace slag
(L)	Mixture of GGBFS and limestone fines