Dam:	Randleman Lake	Country	USA
River	Deep	35°50'4.07"N 79°48'46.49"W	35.834465 -79.812912
Owner/Client	Piedmont Triad Regional Water Authority		
Designer/Engineer	GEI Consultants Inc./Hazen and Sawyer		
Contractor	ASI-RCC, Inc.		

Purpose (code)	R W
Site start	15.07.2001
RCC start	08.04.2002
RCC completion	18.07.2002
Site completion	12.01.2003
Height (m)	31
Length (m)	280
Volume of RCC (m^3x10^3)	70
Total volume (m^3x10^3)	76
Reservoir capacity (m^3x10^6)	84
Upstream slope	V
Forming of upstream face (code)	(1)
Downstream slope	0.75
Forming of downstream face (code)	(1) *
Spillway slope	0.75
Forming of spillway face (code)	(1) *
Depth of layers (mm)	300
Depth of lifts (mm)	300
Cement content (kg/m^3)	89
Pozzolan content (kg/m^3)	104
Code for pozzolan	(F)
RCCDAM Unique Serial No.	RCCDAM0279

Under Construction



RCCDAM0279UC

Completed Dam



RCCDAM0279CD

Google Earth



RCCDAM0279GE

Guide to Abbreviations

Purpose

E	Environmental
F	Flood control
G	Groundwater recharge
H	Flood control
I	Irrigation
N	Navigation
P	Pollution control
R	Recreation
W	Water supply

Facing method

(1)	Traditional concrete against formwork
(2)	Traditional concrete against formwork with external geomembrane
(3)	RCC against formwork
(4)	RCC against formwork with external geomembrane
(5)	Traditional concrete against precast concrete panels
(6)	Traditional concrete against precast concrete panels with geomembrane
(7)	RCC against precast concrete panels
(8)	RCC against precast concrete panels with geomembrane
(9)	RCC against precast concrete panels with hot poured membrane
(10)	RCC against precast concrete blocks
(11)	Reinforced conventional concrete cast before RCC placement
(12)	Reinforced conventional concrete cast after RCC placement
(13)	Reinforced concrete cast against precast units or slip-formed facing elements
(14)	Slip-formed/extruded facing elements
(15)	RCC supported by fill shoulders
(16)	Mechanically compacted unformed face of RCC
(17)	Unformed face of RCC
'	GEVR/GE-RCC
*	Stepped face

Pozzolans

(-)	No Pozzolan Used
(C)	High-lime flyash (ASTM Class C)
(F)	Low-lime flyash (ASTM Class F)
(M)	Milled sand
(N)	Natural pozzolan (ASTM Class N)
(R)	ROLAC (mixture of flyash and slag with or without limestone fines)
(S)	Ground-granulated blast-furnace slag
(L)	Mixture of GGBFS and limestone fines