

Dam: Tirgu Jiu

Country Romania

River Jiu

45°1'57.82"N 23°15'51.35"E

45.032726 23.264263

Owner/Client Romanian Electricity Authority (RENAL) - Tirgu Jiu Branch

Designer/Engineer Institutul de Studii si Proiectari Hidroenergetice (ISPH) Bucuresti

Contractor SC Hidroconstructia SA - Jiu Branch

Purpose (code) H

Site start 01.08.1986

RCC start 01.06.1988

RCC completion 31.05.1989

Site completion 31.12.1993

Height (m) 24

Length (m) 61

Volume of RCC (m³x10³) 13

Total volume (m³x10³) 26

Reservoir capacity (m³x10⁶) 2

Upstream slope *Unknown*

Forming of upstream face (code) (12)

Downstream slope *Unknown*

Forming of downstream face (code) (12)

Spillway slope ogee

Forming of spillway face (code) (12)

Depth of layers (mm) 300

Depth of lifts (mm) 900

Cement content (kg/m³) 125

Pozzolan content (kg/m³) 0

Code for pozzolan (-)

RCCDAM Unique Serial No. RCCDAM0052

Google Earth



RCCDAM0052GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines