Dam:	Zhouba	Country	China
River	Mabianhe	29°5'25.39"N 103°42'46.59"E	29.090385 103.712944
Owner/Client	Chengdu Haineng Power Co. Ltd.		
Designer/Engineer	Institute of Investigation, Design and Research for Hydropower Projects, Chendu		
Contractor	15th Construction Bureau		

Purpose (code)	F H
Site start	01.01.2004
RCC start	01.01.2005
RCC completion	31.12.2006
Site completion	31.12.2007
Height (m)	73
Length (m)	163
Volume of RCC (m^3x10^3)	229
Total volume (m^3x10^3)	405
Reservoir capacity (m^3x10^6)	204
Upstream slope	V
Forming of upstream face (code)	(1)
Downstream slope	0.70
Forming of downstream face (code)	(1)
Spillway slope	0.78
Forming of spillway face (code)	(1)
Depth of layers (mm)	300
Depth of lifts (mm)	300
Cement content (kg/m^3)	110 66
Pozzolan content (kg/m^3)	73 66
Code for pozzolan	(F)
RCCDAM Unique Serial No.	RCCDAM0376

Completed Dam



RCCDAM0376CD

Google Earth



RCCDAM0376GE

Guide to Abbreviations

Purpose

E	Environmental
F	Flood control
G	Groundwater recharge
H	Flood control
I	Irrigation
N	Navigation
P	Pollution control
R	Recreation
W	Water supply

Facing method

(1)	Traditional concrete against formwork
(2)	Traditional concrete against formwork with external geomembrane
(3)	RCC against formwork
(4)	RCC against formwork with external geomembrane
(5)	Traditional concrete against precast concrete panels
(6)	Traditional concrete against precast concrete panels with geomembrane
(7)	RCC against precast concrete panels
(8)	RCC against precast concrete panels with geomembrane
(9)	RCC against precast concrete panels with hot poured membrane
(10)	RCC against precast concrete blocks
(11)	Reinforced conventional concrete cast before RCC placement
(12)	Reinforced conventional concrete cast after RCC placement
(13)	Reinforced concrete cast against precast units or slip-formed facing elements
(14)	Slip-formed/extruded facing elements
(15)	RCC supported by fill shoulders
(16)	Mechanically compacted unformed face of RCC
(17)	Unformed face of RCC
'	GEVR/GE-RCC
*	Stepped face

Pozzolans

(-)	No Pozzolan Used
(C)	High-lime flyash (ASTM Class C)
(F)	Low-lime flyash (ASTM Class F)
(M)	Milled sand
(N)	Natural pozzolan (ASTM Class N)
(R)	ROLAC (mixture of flyash and slag with or without limestone fines)
(S)	Ground-granulated blast-furnace slag
(L)	Mixture of GGBFS and limestone fines